

# FortiGate 2200E Series

FG-2200E and FG-2201E



### Highlights

Gartner Magic Quadrant Leader for both Network Firewalls and SD-WAN.

Security-Driven Networking FortiOS delivers converged networking and security.

Unparalleled Performance with Fortinet's patented / SPU / vSPU processors.

Enterprise Security with consolidated AI / ML-powered FortiGuard Services.

Hyperscale Security to secure any edge at any scale.

### High performance with flexibility

The FortiGate 2200E Series enables organizations to build security-driven networks that can weave security deep into their datacenter and across their hybrid IT architecture to protect any edge at any scale.

Powered by a rich set of AI/ML-based FortiGuard Services and an integrated security fabric platform, the FortiGate 2200E Series delivers coordinated, automated, end-to-end threat protection across all use cases.

The industry's first integrated Zero Trust Network Access (ZTNA) enforcement within an NGFW solution, FortiGate 2200E Series automatically controls, verifies, and facilitates user access to applications delivering consistent convergence with a seamless user experience.

IPS	NGFW	Threat Protection	Interfaces
21.8 Gbps	13.5 Gbps	11 Gbps	Multiple GE RJ45, 25 GE SFP28 / 10 GE SFP+/
			GE SFP, and 40 GE QSFP+ slots



Available in



Appliance



Virtual





Cloud



Container

### **FortiOS Everywhere**

#### FortiOS, Fortinet's advanced operating system

FortiOS enables the convergence of high performing networking and security across the Fortinet Security Fabric. Because it can be deployed anywhere, it delivers consistent and context-aware security posture across network, endpoint, and multi-cloud environments.

FortiOS powers all FortiGate deployments whether a physical or virtual device, as a container, or as a cloud service. This universal deployment model enables the consolidation of many technologies and use cases into a simplified, single policy and management framework. Its organically built best-of-breed capabilities, unified operating system, and ultra-scalability allows organizations to protect all edges, simplify operations, and run their business without compromising performance or protection.

FortiOS dramatically expands the Fortinet Security Fabric's ability to deliver advanced AI/ ML-powered services, inline advanced sandbox detection, integrated ZTNA enforcement, and more, provides protection across hybrid deployment models for hardware, software, and Software-as-a-Service with SASE.

FortiOS expands visibility and control, ensures the consistent deployment and enforcement of security policies, and enables centralized management across large-scale networks with the following key attributes:

- Interactive drill-down and topology viewers that display real-time status
- On-click remediation that provides accurate and quick protection against threats and abuses
- Unique threat score system correlates weighted threats with users to prioritize investigations




Intuitive easy to use view into the network and endpoint vulnerabilities



Visibility with FOS Application Signatures

#### FortiConverter Service

FortiConverter Service provides hassle-free migration to help organizations transition from a wide range of legacy firewalls to FortiGate Next-Generation Firewalls quickly and easily. The service eliminates errors and redundancy by employing best practices with advanced methodologies and automated processes. Organizations can accelerate their network protection with the latest FortiOS technology.



### **FortiGuard Services**

### FortiGuard AI-Powered Security

FortiGuard's rich suite of security services counter threats in real time using Al-powered, coordinated protection designed by FortiGuard Labs security threat researchers, engineers, and forensic specialists.

### Web Security

Advanced cloud-delivered URL, DNS (Domain Name System), and Video Filtering providing complete protection for phishing and other web born attacks while meeting compliance.

Additionally, its dynamic inline CASB (Cloud Access Security Broker) service is focused on securing business SaaS data, while inline ZTNA traffic inspection and ZTNA posture check provide per-sessions access control to applications. It also integrates with the FortiClient Fabric Agent to extend protection to remote and mobile users.

### **Content Security**

Advanced content security technologies enable the detection and prevention of known and unknown threats and file-based attack tactics in real-time. With capabilities like CPRL (Compact Pattern Recognition Language), AV, inline Sandbox, and lateral movement protection make it a complete solution to address ransomware, malware, and credential-based attacks.

#### **Device Security**

Advanced security technologies are optimized to monitor and protect IT, IIoT, and OT (Operational Technology) devices against vulnerability and device-based attack tactics. Its validated near-real-time IPS intelligence detects, and blocks known and zero-day threats, provides deep visibility and control into ICS/OT/SCADA protocols, and provides automated discovery, segmentation, and pattern identification-based policies.

### Advanced Tools for SOC/NOC

Advanced NOC and SOC management tools attached to your NGFW provide simplified and faster time-to-activation.

#### SOC-as-a-Service

Includes tier-one hunting and automation, log location, 24×7 SOC analyst experts, managed firewall and endpoint functions, and alert triage.

#### **Fabric Rating Security Best Practices**

Includes supply chain virtual patching, up-to-date risk and vulnerability data to deliver quicker business decisions, and remediation for data breach situations.



### Secure Any Edge at Any Scale

### Powered by Security Processing Unit (SPU)

Traditional firewalls cannot protect against today's content- and connection-based threats because they rely on off-the-shelf hardware and general-purpose CPUs, causing a dangerous performance gap. Fortinet's custom SPU processors deliver the power you need—up to 520Gbps—to detect emerging threats and block malicious content while ensuring your network security solution does not become a performance bottleneck.

### ASIC Advantage



Network Processor 6 NP6

Fortinet's new breakthrough SPU NP6 network processor works in line with FortiOS functions delivering:

- Superior firewall performance for IPv4/IPv6, SCTP, and multicast traffic with ultra-low latency
- VPN, CAPWAP, and IP tunnel acceleration
- Anomaly-based intrusion prevention, checksum offload, and packet defragmentation
- Traffic shaping and priority queuing



Content Processor 9 CP9

Content Processors act as co-processors to offload resource-intensive processing of security functions. The ninth generation of the Fortinet Content Processor, the CP9, accelerates resource-intensive SSL (including TLS 1.3) decryption and security functions while delivering:

- Pattern matching acceleration and fast inspection of real-time traffic for application identification
- IPS pre-scan/pre-match, signature correlation offload, and accelerated antivirus processing



### FortiCare Services

Fortinet is dedicated to helping our customers succeed, and every year FortiCare Services help thousands of organizations get the most from our Fortinet Security Fabric solution. Our lifecycle portfolio offers Design, Deploy, Operate, Optimize, and Evolve services. Operate services offer device-level FortiCare Elite service with enhanced SLAs to meet our customer's operational and availability needs. In addition, our customized account-level services provide rapid incident resolution and offer proactive care to maximize the security and performance of Fortinet deployments.



### Use Cases

### Next Generation Firewall (NGFW)

- FortiGuard Labs' suite of Al-powered Security Services—natively integrated with your NGFW—secures web, content, and devices and protects networks from ransomware and sophisticated cyberattacks
- Real-time SSL inspection (including TLS 1.3) provides full visibility into users, devices, and applications across the attack surface
- Fortinet's patented SPU (Security Processing Unit) technology provides industry-leading high-performance protection



### Segmentation

- Dynamic segmentation adapts to any network topology to deliver true end-to-end security—from the branch to the datacenter and across multi-cloud environments
- Ultra-scalable, low latency, VXLAN segmentation bridges physical and virtual domains with Layer 4 firewall rules
- Prevents lateral movement across the network with advanced, coordinated protection from FortiGuard Security Services detects and prevents known, zero-day, and unknown attacks



### Secure SD-WAN

- FortiGate WAN Edge powered by one OS and unified security and management framework and systems transforms and secures WANs
- Delivers superior quality of experience and effective security posture for work-from-any where models, SD-Branch, and cloud-first WAN use cases
- Achieve operational efficiencies at any scale through automation, deep analytics, and self-healing



### Mobile Security for 4G, 5G, and IoT

- SPU-accelerated, high performance CGNAT and IPv6 migration options, including: NAT44, NAT444, NAT64/ DNS64, NAT46 for 4G Gi/sGi, and 5G N6 connectivity and security
- RAN Access Security with highly scalable and highest-performing IPsec aggregation and control Security Gateway (SecGW)
- User plane security enabled by full threat protection and visibility into GTP-U inspection

FortiClient

TANA / VPN


FortiClient

</t

Datacenter Deployment (NGFW, IPS, Segmentation)

### Hardware

### FortiGate 2200E Series



Hardware Features



### **High-Speed Connectivity**

High-speed connectivity is essential for network security segmentation at the core of data networks. The FortiGate 2200E Series provides high speed interfaces, simplifying network designs without relying on additional devices to bridge desired connectivity.

### Interfaces

- 1. 1 x USB Port
- 2. 1 x Console Port
- **3.** 2 x GE RJ45 Management Ports
- 4. 12 x GE RJ45 Ports
- 5. 18 × 25 GE SFP28 / 10 GE SFP+ / GE SFP Slots
- 6. 2 × 25 GE SFP28 / 10 GE SFP+ / GE SFP HA Slots
- 7.  $4 \times 40$  GE QSFP+ Slots

## **Specifications**

	FORTIGATE 2200E FORTIGATE 2201E			
Interfaces and Modules				
Hardware Accelerated 40 GE QSFP+ Slots	4			
Hardware Accelerated 25 GE SFP28 / 10 GE SFP+ / GE SFP HA Slots	2			
Hardware Accelerated 25 GE SFP28 / 10 GE SFP+ / GE SFP Slots	18			
Hardware Accelerated GE RJ45 Ports	12			
GE RJ45 Management Ports	2			
USB Port	1			
Console Port	1			
Onboard Storage	0 2×1 TB SSD			
Included Transceivers	2x SFP+ (SR 10 GE)			
System Performance — Enterprise Traffic Mi	ĸ			
IPS Throughput <sup>2</sup>	21.8 Gbps			
NGFW Throughput <sup>2, 4</sup>	13.5 Gbps			
Threat Protection Throughput <sup>2,5</sup>	11 Gbps			
System Performance and Capacity				
IPv4 Firewall Throughput (1518 / 512 / 64 byte, UDP)	158 / 155 / 100 Gbps			
IPv6 Firewall Throughput (1518 / 512 / 86 byte, UDP)	158 / 155 / 100 Gbps			
Firewall Latency (64 byte, UDP)	3.09 µs			
Firewall Throughput (Packet per Second)	150 Mpps			
Concurrent Sessions (TCP)	24 Million			
New Sessions/Second (TCP)	500 000			
Firewall Policies	100 000			
IPsec VPN Throughput (512 byte) <sup>1</sup>	98 Gbps			
Gateway-to-Gateway IPsec VPN Tunnels	20 000			
Client-to-Gateway IPsec VPN Tunnels	100 000			
SSL-VPN Throughput	10 Gbps			
Concurrent SSL-VPN Users (Recommended Maximum, Tunnel Mode)	30 000			
SSL Inspection Throughput (IPS, avg. HTTPS) <sup>3</sup>	17 Gbps			
SSL Inspection CPS (IPS, avg. HTTPS) $^{3}$	9500			
SSL Inspection Concurrent Session (IPS, avg. HTTPS) <sup>3</sup>	2.5 Million			
Application Control Throughput (HTTP 64K) <sup>2</sup>	52 Gbps			
CAPWAP Throughput (HTTP 64K)	60 Gbps			
Virtual Domains (Default / Maximum)	10 / 500			
Maximum Number of FortiSwitches Supported	196			
Maximum Number of FortiAPs (Total / Tunnel)	4096 / 2048			
Maximum Number of FortiTokens	20 000			
High Availability Configurations	Active-Active, Active-Passive, Clustering			

PORTIGATE 2201EPORTIGATE 2201EDimensions and PowerHeight x Width x Length (inches) $3.5 \times 17.44 \times 21.89$ Height x Width x Length (mm) $88.9 \times 443 \times 556$ Weight40.0 lbs (18.2 kg)41.4 lbs (18.8 kg)Form FactorRack Mount, 2 RUAC Power Supply $100-240V$ AC, 50/60 HzPower Consumption (Average / Maximum) $408$ W / 571 W $412$ W / 577 WCurrent (Maximum) $12A@100V$ , 9A@240VHeat Dissipation1948 BTU/h1968 BTU/hRedundant Power Supplies (Hot Swappable)Yes (Default dual AC PSU for 1+1 Redundancy)Power Supply Efficiency Rating $80Plus$ CompliantOperating Temperature $32^\circ$ -104°F ( $0^\circ$ -40°C)Storage Temperature $-31^\circ$ -158°F ( $-35^\circ$ -70°C)Humidity $10\%$ -90% non-condensingNoise Level70 dBAForced AirflowFront to BackOperating AltitudeUp to 7400 ft (2250 m)ComplianceFCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CBCertificationsUSGv6/IPv6					
Height x Width x Length (inches)       3.5 × 17.44 × 21.89         Height x Width x Length (mm)       88.9 × 443 × 556         Weight       40.0 lbs (18.2 kg)       41.4 lbs (18.8 kg)         Form Factor       Rack Mount, 2 RU         AC Power Supply       100–240V AC, 50/60 Hz         Power Consumption (Average / Maximum)       408 W / 571 W       412 W / 577 W         Current (Maximum)       12A@100V, 9A@240V         Heat Dissipation       1948 BTU/h       1968 BTU/h         Redundant Power Supplies (Hot Swappable)       Yes (Default dual AC PSU for 1+1 Redundancy)         Power Supply Efficiency Rating       80Plus Compliant         Operating Temperature       32°-104°F (0°-40°C)         Storage Temperature       -31°-158°F (-35°-70°C)         Humidity       10%-90% non-contensing         Noise Level       70 dBA         Forced Airflow       Front to Back         Operating Altitude       Up to 7400 ft (2250 m)         Compliance       FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB		FORTIGATE 2200E	FORTIGATE 2201E		
Height x Width x Length (mm)         88.9 × 443 × 556           Weight         40.0 lbs (18.2 kg)         41.4 lbs (18.8 kg)           Form Factor         Rack Mount, 2 RU           AC Power Supply         100–240V AC, 50/60 Hz           Power Consumption (Average / Maximum)         408 W / 571 W         412 W / 577 W           Current (Maximum)         12A@100V, 9A@240V           Heat Dissipation         1948 BTU/h         1968 BTU/h           Redundant Power Supplies (Hot Swappable)         Yes (Default dual AC PSU for 1+1 Redundancy)           Power Supply Efficiency Rating         80Plus Compliant           Operating Temperature         32°–104°F (0°–40°C)           Storage Temperature         -31°–158°F (-35°–70°C)           Humidity         10%–90% non-condensing           Noise Level         70 dBA           Forced Airflow         Front to Back           Operating Altitude         Up to 7400 ft (2250 m)           Compliance         FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Dimensions and Power				
Noight Nitherin Europic (min)Sole of the loceWeight40.0 lbs (18.2 kg)41.4 lbs (18.8 kg)Form FactorRack Mount, 2 RUAC Power Supply100-240V AC, 50/60 HzPower Consumption (Average / Maximum)408 W / 571 W412 W / 577 WCurrent (Maximum)12A@100V, 9A@240VHeat Dissipation1948 BTU/h1968 BTU/hRedundant Power Supplies (Hot Swappable)Yes (Default dual AC PSU for 1+1 Redundancy)Power Supply Efficiency Rating80Plus CompliantOperating Temperature32°-104°F (0°-40°C)Storage Temperature-31°-158°F (-35°-70°C)Humidity10%-90% non-condensingNoise Level70 dBAForced AirflowFront to BackOperating AltitudeUp to 7400 ft (2250 m)ComplianceFCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Height x Width x Length (inches)	3.5 × 17.4	4 × 21.89		
Form Factor         Rack Mount, 2 RU           AC Power Supply         100–240V AC, 50/60 Hz           Power Consumption (Average / Maximum)         408 W / 571 W         412 W / 577 W           Current (Maximum)         12A@100V, 9A@240V           Heat Dissipation         1948 BTU/h         1968 BTU/h           Redundant Power Supplies (Hot Swappable)         Yes (Default dual AC PSU for 1+1 Redundancy)           Power Supply Efficiency Rating         80Plus Compliant           Operating Environment and Certifications            Operating Temperature         32°–104°F (0°–40°C)           Storage Temperature         -31°–158°F (-35°–70°C)           Humidity         10%–90% non-condensing           Noise Level         70 dBA           Forced Airflow         Front to Back           Operating Altitude         Up to 7400 ft (2250 m)           Compliance         FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Height x Width x Length (mm)	88.9 × 443 × 556			
AC Power Supply100–240V AC, 50/60 HzPower Consumption (Average / Maximum)408 W / 571 W412 W / 577 WCurrent (Maximum)12A@100V, 9A@240VHeat Dissipation1948 BTU/h1968 BTU/hRedundant Power Supplies (Hot Swappable)Yes (Default dual AC PSU for 1+1 Redundancy)Power Supply Efficiency Rating80Plus CompliantOperating Environment and Certifications20Operating Temperature32°–104°F (0°–40°C)Storage Temperature-31°–158°F (-35°–70°C)Humidity10%–90% non-condensingNoise Level70 dBAForced AirflowFront to BackOperating AltitudeUp to 7400 ft (2250 m)ComplianceFCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Weight	40.0 lbs (18.2 kg)	41.4 lbs (18.8 kg)		
Power Consumption (Average / Maximum)         408 W / 571 W         412 W / 577 W           Current (Maximum)         12A@100V, 9A@240V           Heat Dissipation         1948 BTU/h         1968 BTU/h           Redundant Power Supplies (Hot Swappable)         Yes (Default dual AC PSU for 1+1 Redundancy)           Power Supply Efficiency Rating         80Plus Compliant           Operating Environment and Certifications         0           Operating Temperature         32°-104°F (0°-40°C)           Storage Temperature         -31°-158°F (-35°-70°C)           Humidity         10%-90% non-condensing           Noise Level         70 dBA           Forced Airflow         Front to Back           Operating Altitude         Up to 7400 ft (2250 m)           Compliance         FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Form Factor	Rack Mount, 2 RU			
(Average / Maximum)       12A@100V, 9A@240V         Current (Maximum)       12A@100V, 9A@240V         Heat Dissipation       1948 BTU/h       1968 BTU/h         Redundant Power Supplies       Yes (Default dual AC PSU for 1+1 Redundancy)         Power Supply Efficiency Rating       80Plus Compliant         Operating Environment and Certifications       0         Operating Temperature       32°-104°F (0°-40°C)         Storage Temperature       -31°-158°F (-35°-70°C)         Humidity       10%-90% non-condensing         Noise Level       70 dBA         Forced Airflow       Front to Back         Operating Altitude       Up to 7400 tt (2250 m)         Compliance       FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	AC Power Supply	100-240V AC, 50/60 Hz			
Heat Dissipation     1948 BTU/h     1968 BTU/h       Redundant Power Supplies (Hot Swappable)     Yes (Default dual AC PSU for 1+1 Redundancy)       Power Supply Efficiency Rating     80Plus Compliant       Operating Environment and Certifications     0       Operating Temperature     32°-104°F (0°-40°C)       Storage Temperature     -31°-158°F (-35°-70°C)       Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB		408 W / 571 W	412 W / 577 W		
Redundant Power Supplies (Hot Swappable)     Yes (Default dual AC PSU for 1+1 Redundancy)       Power Supply Efficiency Rating     80Plus Compliant       Operating Environment and Certifications     000000000000000000000000000000000000	Current (Maximum)	12A@100V, 9A@240V			
(Hot Swappable)     (Default dual AC PSU for 1+1 Redundancy)       Power Supply Efficiency Rating     80Plus Compliant       Operating Environment and Certifications     32°-104°F (0°-40°C)       Storage Temperature     -31°-158°F (-35°-70°C)       Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Heat Dissipation	1948 BTU/h	1968 BTU/h		
Operating Environment and Certifications       Operating Temperature     32°-104°F (0°-40°C)       Storage Temperature     -31°-158°F (-35°-70°C)       Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB		100			
Operating Temperature     32°-104°F (0°-40°C)       Storage Temperature     -31°-158°F (-35°-70°C)       Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Power Supply Efficiency Rating	80Plus Compliant			
Storage Temperature     -31°-158°F (-35°-70°C)       Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Operating Environment and Certifications				
Humidity     10%-90% non-condensing       Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Operating Temperature	32°-104°F (0°-40°C)			
Noise Level     70 dBA       Forced Airflow     Front to Back       Operating Altitude     Up to 7400 ft (2250 m)       Compliance     FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Storage Temperature	-31°-158°F (-35°-70°C)			
Forced Airflow         Front to Back           Operating Altitude         Up to 7400 ft (2250 m)           Compliance         FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Humidity	10%-90% non-condensing			
Operating Altitude         Up to 7400 ft (2250 m)           Compliance         FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Noise Level	70 dBA			
Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Forced Airflow	Front to Back			
CE, UL/cUL, CB	Operating Altitude	Up to 7400 ft (2250 m)			
Certifications USGv6/IPv6	Compliance				
	Certifications	USGv6/IPv6			

Note: All performance values are "up to" and vary depending on system configuration. <sup>1</sup> IPsec VPN performance test uses AES256-SHA256.

 $^{\rm 2}$  IPS (Enterprise Mix), Application Control, NGFW and Threat Protection are measured with Logging enabled.

 $^{\scriptscriptstyle 3}$  SSL Inspection performance values use an average of HTTPS sessions of different cipher suites.



<sup>5</sup> Threat Protection performance is measured with Firewall, IPS, Application Control and Malware Protection enabled.

# **Ordering Information**

Product	SKU	Description
FortiGate 2200E	FG-2200E	4× 40 GE QSFP+ slots, 20× 25 GE SFP28 slots (including 18x ports, 2x HA ports), 14x GE RJ45 ports (including 12x ports, 2x management ports), SPU NP6 and CP9 hardware accelerated, and dual AC power supplies.
FortiGate 2201E	FG-2201E	$4\times$ 40 GE QSFP+ slots, 20× 25 GE SFP28 slots (including 18x ports, 2x HA ports), 14x GE RJ45 ports (including 12x ports, 2x management ports), SPU NP6 and CP9 hardware accelerated, and dual AC power supplies, with 2× 1 TB SSD onboard storage.
Optional Accessories	SKU	Description
10 GE SFP+ RJ45 Transceiver Module	FN-TRAN-SFP+GC	10 GE SFP+ RJ45 transceiver module for systems with SFP+ slots.
10 GE SFP+ Transceiver Module, Short Range	FN-TRAN-SFP+SR	10 GE SFP+ transceiver module, short range for all systems with SFP+ and SFP/SFP+ slots.
10 GE SFP+ Transceiver Module, Long Range	FN-TRAN-SFP+LR	10 GE SFP+ transceiver module, long range for all systems with SFP+ and SFP/SFP+ slots.
10 GE SFP+ Transceiver Module, Extended Range	FN-TRAN-SFP+ER	10 GE SFP+ transceiver module, extended range for all systems with SFP+ and SFP/SFP+ slots.
10 GE SFP+ Active Direct Attach Cable, 10m / 32.8 ft	SP-CABLE-ADASFP+	10 GE SFP+ active direct attach cable, 10m / 32.8 ft for all systems with SFP+ and SFP/SFP+ slots.
25 GE SFP28 Transceiver Module, Short Range	FN-TRAN-SFP28-SR	25 GE SFP28 transceiver module, short range for all systems with SFP28 slots.
25 GE SFP28 Transceiver Module, Long Range	FG-TRAN-SFP28-LR	25 GE SFP28 transceiver module, long range for all systems with SFP28 slots
40 GE QSFP+ Transceiver Module, Short Range	FN-TRAN-QSFP+SR	40 GE QSFP+ transceiver module, short range for all systems with QSFP+ slots.
40 GE QSFP+ Transceivers, Short Range, BiDi	FG-TRAN-QSFP+SR-BIDI	40 GE QSFP+ transceivers, short range BiDi for systems with QSFP+ slots.
40 GE QSFP+ Transceiver Module, Long Range	FN-TRAN-QSFP+LR	40 GE QSFP+ transceiver module, long range for all systems with QSFP+ slots.
40 GE QSFP+ to 4× 10 GE SFP+ Optical Breakout	FG-TRAN-QSFP+4XSFP	40 GE QSFP+ Parallel Breakout Active Optical Cable with 1m length for all systems with QSFP+ slots.
40 GE QSFP+ Passive Direct Attach Cable	SP-CABLE-FS-QSFP+(1/3/5)	40GE QSFP+ Passive Direct Attach Cable, (1/3/5 m) for Systems with QSFP+ slots.
QSFP+ to 4xSFP+ Optical breakout 5m	FG-TRAN-QSFP+4SFP-5	40 G QSFP+ Parallel Breakout MPO to 4xLC connectors, 5m reach, transceivers not included.
Rack Mount Sliding Rails	SP-FG3040B-RAIL	Rack mount sliding rails for FG-1000C/-DC, FG-1100/1101E, FG-1200D, FG-1500D/-DC, FG-2000E, FG-2200E/2201E, FG-2500E, FG-3040B/-DC, FG-3140B/-DC, FG-3240C/-DC, FG-3000D/-DC, FG-3100D/-DC, FG-3200D/-DC, FG-3300E/3301E, FG-3400/3401E, FG-3600/3601E, FG-3700D/-DC, FG-3700D/-DC, FG-3700DX, FG-3810D/-DC and FG-3950B/-DC.
AC Power Supply	SP-FG3800D-PS	AC power supply for FG-2200/2201E, FG-3300/3301E, FG-3400/3401E, FG-3600/3601E, FG-3700D, FG-3700D-NEBS, FG-3700DX, FG-3810D and FG-3815D.

# Subscriptions

				Bundles		
Service Category	Service Offering	A-la-carte	Enterprise Protection	Unified Threat Protection	Advanced Threat Protection	
Security Services	FortiGuard IPS Service	•	•	•	•	
	FortiGuard Anti-Malware Protection (AMP) — Antivirus, Mobile Malware, Botnet, CDR, Virus Outbreak Protection and FortiSandbox Cloud Service			•	•	
	FortiGuard Web Security — URL and web content, Video and Secure DNS Filtering	•	•	•		
	FortiGuard Anti-Spam		•	•		
	FortiGuard IoT Detection Service	•	•			
	FortiGuard Industrial Security Service	•	•			
	FortiCloud AI-based Inline Sandbox Service <sup>1</sup>	•				
NOC Services	FortiGate Cloud (SMB Logging + Cloud Management)	•				
	FortiGuard Security Fabric Rating & Compliance Monitoring Service	•	•			
	FortiConverter Service	•	•			
	FortiGuard SD-WAN Underlay Bandwidth and Quality Monitoring Service	•				
SOC Services	FortiAnalyzer Cloud	•				
	FortiAnalyzer Cloud with SOCaaS	•				
Hardware and Software Support	FortiCare Essentials	•				
	FortiCare Premium	•	٠	•	•	
	FortiCare Elite	•				
Base Services	FortiGuard Application Control					
	FortiCloud ZTNA Inline CASB Service 1					
	Internet Service (SaaS) DB Updates	is shull alwith FastiOans Out a 111				
	GeoIP DB Updates	included with FortiCare Subscription				
	Device/OS Detection Signatures					
	Trusted Certificate DB Updates					
	DDNS (v4/v6) Service					

1. Available when running FortiOS 7.2



### FortiGuard Bundles


FortiGuard Labs delivers a number of security intelligence services to augment the FortiGate firewall platform. You can easily optimize the protection capabilities of your FortiGate with one of these FortiGuard Bundles.

### FortiCare Elite

FortiCare Elite services offers enhanced service-level agreements (SLAs) and accelerated issue resolution. This advanced support offering provides access to a dedicated support team. Single-touch ticket handling by the expert technical team streamlines resolution. This option also provides Extended End-of-Engineering-Support (EoE's) of 18 months for added flexibility and access to the new FortiCare Elite Portal. This intuitive portal provides a single unified view of device and security health.

### Fortinet CSR Policy

Fortinet is committed to driving progress and sustainability for all through cybersecurity, with respect for human rights and ethical business practices, making possible a digital world you can always trust. You represent and warrant to Fortinet that you will not use Fortinet's products and services to engage in, or support in any way, violations or abuses of human rights, including those involving illegal censorship, surveillance, detention, or excessive use of force. Users of Fortinet products are required to comply with the Fortinet EULA and report any suspected violations of the EULA via the procedures outlined in the Fortinet Whistleblower Policy.





www.fortinet.com

Copyright © 2023 Fortinet, Inc. All rights reserved. FortiGate<sup>6</sup>, Fortinet<sup>6</sup>, Fortinet<sup>6</sup>